

## DKM-SX17U Rack Console

Monitor Keyboard Mouse with Flip-up 17" LCD, Pull-out USB Keyboard

### Features

- » Rack console with LCD monitor, USB keyboard and touchpad mouse.
- » Slide-out rack mount drawer designed for 19 inch racks.
- » Monitor and keyboard take up only 1U rack space.
- » Flip-up 17" LCD @ 1280 x 1024 pixels SXGA resolution.
- » Built-in speakers and audio connector.
- » Front bezel control buttons for display adjustment.
- » Only 17.75" depth.
- » Detachable slide rails with adjustable mounting brackets (16.5" to 30")

### Single Point Server Management

The DKM-SX17U is a rack-mountable flat panel LCD monitor that occupies only 1 rack unit space. Using a flip-up monitor design, the DKM-SX17U offers a low profile rack mount console for your server. The slide-out LCD monitor and keyboard drawer is mounted on slide rails so you can easily pull the unit out of your equipment rack. The LCD monitor flips up for use and folds down for storage.

The DKM-SX17U provides you with a USB keyboard and touchpad mouse. There is a built-in USB hub supporting two additional USB ports conveniently located on the keyboard tray, you have easily accessible USB ports right in front of the LCD monitor, without having to reach to the back of your server.

The DKM-SX17U keyboard video mouse has a 17" SXGA flat panel display. The LCD's lower power consumption and EMI free technology makes it ideal for industrial applications. And with its native resolution of 1280 x 1024 pixels, you can work more and scroll less, because you can put more information on screen instead of cluttering it with menus and tool bars. An on-screen display (OSD) menu using four front-panel-mounted control buttons let's you adjust the display for optimum viewing.

The entire keyboard video mouse rackmount drawer is constructed of metal for ruggedness. At just over 17" in depth, you can fit the unit in short-depth cabinets. With the rear mounting brackets that can be extended from 16.5" up to 30", it will also accommodate the deepest equipment racks.



# DKM-SX17U Rack Console

## Technical Specifications

### Physical Specifications

<i>Chassis</i>	1U slide-out rack mount drawer with LCD monitor, USB keyboard and touchpad mouse. Rugged metal construction. Keyboard drawer lock prevents unauthorized access to the console.
<i>Mounting Options</i>	Rugged metal construction slide-out rackmountable drawer. Flip-up LCD monitor.
<i>Form Factor</i>	1U rack-mountable.
<i>Electrical and Power</i>	Autosensing AC power supply.
<i>External Controls</i>	Front bezel OSD menu controls for LCD contrast, brightness, image position, color temperature, language, focus. LCD backlight on/off button.
<i>I/O Connectors</i>	D-Sub 15-pin VGA, USB connectors for keyboard and mouse.
<i>Dimensions</i>	19.0" (W) x 1.75" (H) x 17.75" (D)
<i>Weight</i>	25.5 lbs. (33 lbs. shipping weight with all included accessories),

Rear mounting brackets extends from 16.5" to 30.25" via adjustable extension piece.

### Flat Panel LCD Specifications

<i>Display Type</i>	Active matrix TFT LCD. Protected by anti-glare tempered glass.
<i>Display Size</i>	17-inch screen (measured diagonally).
<i>Resolution</i>	1280 x 1024 optimum resolution (SXGA).
<i>Color Depth</i>	24-bit color depth (16 million colors).
<i>Contrast Ratio</i>	350:1
<i>Viewing Angles</i>	160/160 (vertical/horizontal)
<i>LCD Backlight MTBF</i>	50,000 hours @ 25±5 °C
<i>Input Signal</i>	Analog RGB, VGA ~ SXGA
<i>Vertical Sync</i>	60 ~ 70Hz

### Environmental, Safety

<i>ESD/EMI/EMC/Safety</i>	UL, CE, FCC.
<i>Operating Temperature</i>	32 ~ 122 °F
<i>Storage Temperature</i>	-40 ~ 158 °F